


# 9873 FLUSHING OIL



Textiles

## DESCRIPTION

Yellow fluid.

## APPLICATIONS

Cleaning of circular latch needle knitting machines.

## APPLICATION DETAILS

9873 FLUSHING OIL should be used just as supplied by applying it to the needles and cam tracks. In the case of heavy contamination, it is recommended that a quantity of waste should be knitted after applying the flushing oil. Where contamination is not excessive, it is expected to be possible to continue knitting in the normal way as the self-emulsifying characteristics of 9873 FLUSHING OIL will assist in its subsequent removal, together with the normal needle lubricant, during fabric scouring.

Re-oiling with normal lubricant should be carried out after cleaning with 9873 FLUSHING OIL.

## PERFORMANCE DATA

- The low viscosity ensures easy penetration into the knitting elements.
- Helps to soften and remove deposits of dirt, fibre, oxidized oil, etc.
- Non-corrosive to machinery parts.

## TYPICAL CHARACTERISTICS AND PROPERTIES

9873 FLUSHING OIL	UNITS	TYPICAL RESULT
Viscosity @ 40°C	cSt	Approx. 8
Density @ 15°C	kg/l	Approx. 0.837
Flash Point (SETA)	°C	> 120
Ionic Character		Non-ionic / Anionic
Emulsifiability		Emulsifies readily in water
Shelf Life		7 years in original container stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Fax:** +44 (0) 113 386 7676  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [techserv@vickers-oil.com](mailto:techserv@vickers-oil.com)

Accredited to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717