

SPOTLESS NX15



Textiles

DESCRIPTION

Fluid, mineral based machine lubricant. Self-emulsifiable in water.

APPLICATIONS

Lubrication of needles, sinkers and cams of large diameter circular knitting machines, including electronic machines. Also suitable for flat bed knitting machines where an ISO VG 15 lubricant is specified and recommended for the knitting of cotton, cotton / synthetic or 100% synthetic fabrics which will receive an aqueous scour and the production of elastane fabrics.

APPLICATION DETAILS

Suitable for use with the automatic oiling units commonly fitted to knitting machines. It is recommended that the machine manufacturers' guidelines are followed with respect to the oil application rates.

PERFORMANCE DATA

- Based on high quality, highly refined mineral oil incorporating an anti-oxidation additive system. The oil has excellent stability, resisting oxidation and breakdown of the oil even at prolonged high operating temperatures.
- Incorporates an effective anti-wear additive system which provides a very high standard of protection under the boundary lubricating conditions normally associated with knitting machines needles and cams.
- Contains anti-corrosion additives and is non-corrosive to the metals normally used for textile machinery.
- The oil is self emulsifiable in water and can therefore be expected to provide a high standard of scouring performance from knitted fabrics. A detergent with alkali scour system is recommended.
- SPOTLESS NX15 is formulated to have good compatibility with the rubber seals, plastic and electronic components that may be incorporated in modern machinery.
- SPOTLESS NX technology has been tested by DuPont laboratories and has been found to be compatible with Lycra. The oil is suitable for production of elastane fabrics which may be pre-scoured or pre-set.

NOTES

When introducing a new oil to a machine we recommend cleaning the original oil from the machine and oiler unit as thoroughly as possible, to avoid the potential of any incompatibility problems.

SPOTLESS NX15 has been formulated and tested to have good compatibility with knitting machine components. However, as with any oil, it is not possible to guarantee full resistance of all materials with which the oil may come into contact with the practice.

BENJ^m R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

SPOTLESS NX15



TYPICAL CHARACTERISTICS AND PROPERTIES

| SPOTLESS NX15 | UNITS | TYPICAL RESULT |
|--------------------|-------|---|
| Colour | | Colourless to pale yellow |
| Viscosity @ 40°C | cSt | Approx. 15 (ISO15) |
| Density @ 15°C | kg/l | Approx. 0.852 |
| Cloud Point | °C | < 0 |
| Flash Point (SETA) | °C | > 130 |
| Ionic Character | | Non-ionic / Cationic |
| Emulsifiability | | Self-emulsifiable in water |
| Shelf Life | | 7 years in original container stored out of direct sunlight |

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if used in any other applications.

BENJ^m R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard

