

VICKERLUBE FG CHAIN OIL 100



PART NUMBER

40747

DESCRIPTION

VICKERLUBE FG CHAIN OIL 100 is a high performance, pharmaceutical white oil based, food grade chain lubricant, with anti-wear and EP additives registered to H1 for incidental food contact for use in and around food, beverage and pharmaceutical processing and production areas.

APPLICATIONS

It is designed for chains on equipment and machinery in the food and clean industries operating at a wide temperature range. The lubricant has high resistance to wear and load and also has good water resistance. It is ideal for applications where water wash down is present and the additive package gives enhanced protection against wear and load and supports the users' requirements for HACCP and GMP programmes.

Applications include: -

- All Chain types
- Sprockets
- Oil lubricated bearings
- Valves
- Multipurpose lubrication including central lubricators

CERTIFICATION

VICKERLUBE FG CHAIN OIL 100 is NSF H1 Registered – 162113, for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and ISO 21469 and meets the requirements of FDA 21 CFR 178.3570.

FEATURES AND BENEFITS

- | | |
|-------------------------------------|--|
| • H1 Registered | Safe to use where incidental food contact may occur |
| • Excellent wear protection | Elongates chain life |
| • Oxidation and corrosion inhibited | Increases oil life & protects chains against corrosion |
| • Excellent water resistance | Elongates chain life |

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

VICKERLUBE FG CHAIN OIL 100



METHOD OF APPLICATION

VICKERLUBE FG CHAIN OIL 100 can be applied manually, by brush, or through a drip feed or pressurised central lubrication system capable of dispensing an ISO 100 lubricant.

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG CHAIN OIL 100	TEST METHOD	RESULT
Appearance	Visual	Clear Yellow liquid
Viscosity at 40°C	ASTM D7042	100 cSt
Viscosity Index	ASTM D2270	105
Flash Point - COC	ASTM D92	260°C
Pour Point	ASTM D97	-15°C
Copper Strip Corrosion 3h @ 100°C	ASTM D130	1a
Steel Corrosion	ASTM D665B	Pass
4 Ball Wear Scar Diameter	ASTM D4172	0.34 mm
4 Ball Weld Load	ASTM D2783	160 kg
Temperature Range		-5°C to 140°C
Shelf Life		5 years in original sealed containers whilst stored out of direct sunlight



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom
Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717