

# VICKERLUBE FG MULTI-TAK



## PART NUMBER

25901

## DESCRIPTION

VICKERLUBE FG MULTI-TAK is a high temperature semi-synthetic, inorganic thickened, non metallic food grade assembly, anti-seize and open gear lubricant. It is registered to H1 for incidental food contact for use in and around food, beverage and pharmaceutical processing and production areas.

## APPLICATIONS

It is designed for use on components and machinery in the food and clean industries operating at high temperatures. The product has extremely high temperature resistance and high load carrying properties. It is ideal for anti-seize applications where high temperature and humidity are present as well as an excellent lubricant for open gears and rack and pinion type applications. The solid additives, including PTFE, give enhanced protection against wear and load. Applications include: -

- Threads as anti-seize
- Open gears
- Studs and flanges
- Slides, guides and spindles
- Cams and followers
- Heavy duty sliding surfaces

## CERTIFICATION

VICKERLUBE FG MULTI-TAK is NSF H1 Registered -161530, for direct food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015.

## FEATURES AND BENEFITS

- |                                     |   |
|-------------------------------------|---|
| • H1 Registered                     | Safe to use where incidental food contact may occur |
| • No dropping point                 | Product stays in place at elevated temperatures     |
| • Extreme temperature resistance    | Suitable for extreme temperature applications       |
| • PTFE fortified                    | Excellent wear resistance                           |
| • Extreme Pressure properties       | Good load carrying, protection against shock loads  |
| • Oxidation and corrosion inhibited | Increases life & protects parts against corrosion   |

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on   

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



# VICKERLUBE FG MULTI-TAK



## METHOD OF APPLICATION

VICKERLUBE FG MULTI-TAK should be applied sparingly as a thin film using a brush or lint-free cloth.

## TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG MULTI-TAK	TEST METHOD	RESULT
Appearance	Visual	Smooth White Paste
Thickener		Inorganic
Base Oil		Synthetic
4 Ball Weld Load	ASTM D2596	600 Kg
Coefficient of Friction		0.12
Temperature Range, as a service lubricant		-30°C to 150°C
Temperature Range, as an anti-seize		-30°C to 1100°C
Shelf Life		2 years in original sealed containers whilst stored out of direct sunlight



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

### BENJ<sup>n</sup> R. VICKERS & SONS LTD.

**Registered Office**  
 6 Clarence Road, Leeds,  
 LS10 1ND, United Kingdom

**Registered in England**  
 Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on 

Certified to the ISO 9001  
 Quality Standard and the  
 ISO 14001 Environmental  
 Management Standard



FM 01851 EMS 40717