



Trusted for Generations

H.S.T.N: 34039900
REF: MKT.PDS.121
REV: 2

VICKERLUBE FG SUGARSOL



PART NUMBER

45364

DESCRIPTION

VICKERLUBE FG SUGARSOL is low viscosity product formulated to remove deposits of sugar in the confectionary and sugar industries. It leaves a light lubricating film behind to protect components and equipment against further foodstuffs adhering to surfaces.

APPLICATIONS

VICKERLUBE FG SUGARSOL is designed as a protection and cleaning agent in applications such as:

- Confectionary Industry – initial cleaning of sticky surfaces after machine operation
- Mould release agent – confectionary, chocolate etc.
- Cutters on saw blades, circular saws, chains, conveyor bands, blender surfaces etc.
- Beverage industry – fillers and cappers protected against syrups and sugars

The product is suitable for use from -5°C to 80°C.

CERTIFICATION

VICKERLUBE FG SUGARSOL is H1 Registered for incidental food contact, Halal Certified, Kosher Certified, and manufactured to ISO 9001:2015 and ISO 21469.

FEATURES AND BENEFITS

- | | |
|---|---|
| • H1 Registered* | Safe to use where incidental food contact may occur |
| • Excellent sugar dissolving properties | Prevents separation and crystallisation |
| • Corrosion inhibited | Protects against corrosion |
| • Light lubrication properties | Prevents further corrosion and stick slip |

METHOD OF APPLICATION

VICKERLUBE FG SUGARSOL can be applied by brushing, dripping, spraying, dipping or by centralised lubrication systems.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717



Trusted for Generations

H.S.T.N: 34039900
REF: MKT.PDS.121
REV: 2

VICKERLUBE FG SUGARSOL



TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG SUGARSOL	TEST METHOD	RESULT
Appearance	Visual	Clear and Bright
Density at 15°C (kg/l)	ASTM D4052	1.04
Viscosity @ 40°C (cSt)	ASTM D7042	4
Pour Point (°C)	ASTM D7346	-15
Shelf Life		5 years in original sealed containers stored out of direct sunlight

* NSF registration pending.

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717