

# VICKERLUBE FG UNIVERSAL OIL 32



## PART NUMBER

45782

## DESCRIPTION

VICKERLUBE FG UNIVERSAL OIL 32 is a premium quality, medicinal white oil registered to H1 for incidental food contact, for use in and around food, beverage, and pharmaceutical production areas.

## APPLICATIONS

VICKERLUBE FG UNIVERSAL OIL 32 is designed for use in the food, beverage and pharmaceutical industries where there is a chance of incidental food contact.

It is primarily intended for wash down and short term (overnight) corrosion protection and light lubrication for food manufacturing equipment.

## CERTIFICATION

VICKERLUBE FG UNIVERSAL OIL 32 is NSF H1 Registered - 162304, for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and meets the requirements of FDA 21 CFR 172.878 and 21 CFR 178.3620(a).

## FEATURES AND BENEFITS

- |                              |   |
|------------------------------|---|
| • H1 Registered              | Safe to use where incidental food contact may occur |
| • Protects against corrosion | Increased component life                            |
| • Non-odour or tainting      | No effect on food stuff                             |

## METHOD OF APPLICATION

VICKERLUBE FG UNIVERSAL OIL 32 can be applied manually by brush, in a trigger spray or pressurised lubrication system capable of pumping an ISO VG 32 fluid.

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on   

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717



Trusted for Generations

H.S.T.N: 27101985  
REF: MKT.PDS.115  
REV: 4

# VICKERLUBE FG UNIVERSAL OIL 32



## TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG UNIVERSAL OIL 32	TEST METHOD	RESULT
Appearance	Visual	Clear and Bright
Density at 15°C (g/cm <sup>3</sup> )	ASTM D4052	0.86
Viscosity at 40°C (cSt)	ASTM D7042	32
Flash Point (°C)	ASTM D92	>185
Pour Point (°C)	ASTM D7347	<-9
Shelf Life		3 years in original sealed containers stored out of direct sunlight



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

### BENJ<sup>n</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717