

VICKERLUBE FGS GEAR OIL SERIES



PART NUMBER

15672 (ISO 100)	15311 (ISO 150)
15428 (ISO 220)	15544 (ISO 320)
15626 (ISO 460)	15788 (ISO 680)

DESCRIPTION

VICKERLUBE FGS GEAR OILS are high-performance PAO synthetic oils. They are formulated with the latest additive technology giving outstanding extreme pressure properties and load carrying, along with an outstanding wide operating temperature range. They are registered to H1 for incidental food contact for use in gearboxes and applications in and around food, beverage and pharmaceutical processing and production areas. VICKERLUBE FGS GEAR OIL 460 is suited to low-speed, high-load applications such as worm and wheel gearboxes.

APPLICATIONS

VICKERLUBE FGS GEAR OILS are designed for gearboxes and gear systems in the food and clean industries, operating at wide temperature ranges and under high load. The lubricants have high resistance to wear and temperature extremes. The additive package gives enhanced corrosion protection properties and supports manufacturers requirements for HACCP and GMP programmes.

Applications include: -

- All Gearbox types
- High and Low temperature applications (Freezers and Ovens)
- Gears for conveyors
- Agitators, mixers, and fillers
- Extruders
- High loaded oil lubricated bearings

CERTIFICATION

VICKERLUBE FGS GEAR OILS are NSF H1 Registered for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and ISO 21469 and meet the requirements of FDA 21 CFR 178.3570.

NSF Registration (ISO 100) - 163600

NSF Registration (ISO 150) - 161653

NSF Registration (ISO 220) - 161348

NSF Registration (ISO 320) - 161767

NSF Registration (ISO 460) - 161768

NSF Registration (ISO 680) - 163536

FEATURES AND BENEFITS

- | | |
|-------------------------------------|---|
| • H1 Registered | Safe to use where incidental food contact may occur |
| • Excellent water resistance | Extends bearing, gears and gearbox life |
| • Wide operating temperature | Extends life at temperature extremes |
| • Excellent shear stability | Elongates lubricant life |
| • Good air release properties | Enhanced lubricity and elongates component life |
| • Excellent wear protection | Elongates gears and bearing life |
| • Oxidation and corrosion inhibited | Increases oil life & protects gearbox against corrosion |

BENJ^N R. VICKERS & SONS LTD.

Registered Office

6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England

Company No. 00130013

Tel: +44 (0) 113 386 7654

Web: www.vickers-oil.com

Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

VICKERLUBE FGS GEAR OIL SERIES



METHOD OF APPLICATION

VICKERLUBE FGS GEAR OILS can be poured directly from the container, or if using a drum, please ensure clean equipment is used to transfer product to the gearbox.

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FGS GEAR OIL	TEST METHOD	100	150	220
Appearance	Visual	---Clear and Bright---		
Viscosity at 40°C (cSt)	ASTM D445	100	150	220
Viscosity at 100°C (cSt)	ASTM D445	16	22	30
Viscosity Index	ASTM D2270	161	170	175
Density at 15°C (g/cm ³)	ASTM D1298	0.84	0.85	0.85
Pour Point (°C)	ASTM D97	-45	-35	-34
Flash Point (°C)	ASTM D92	212	247	254
Copper Strip Corrosion 3h @ 100°C	ASTM D130	1a	1a	1a
Demulsibility (minutes)	ASTM D1401	10	15	15
4 Ball Wear Scar Diameter (mm)	ASTM D4172	0.35	0.43	0.35
Temperature Range (°C)	-	-35 to 160	-25 to 160	-25 to 160

Shelf Life - 5 years in original sealed containers whilst stored out of direct sunlight

BENJ^N R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom

Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on 

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717

VICKERLUBE FGS GEAR OIL SERIES



VICKERLUBE FGS GEAR OIL	TEST METHOD	320	460	680
Appearance	Visual	---Clear and Bright---		
Viscosity at 40°C (cSt)	ASTM D445	320	460	652
Viscosity at 100°C (cSt)	ASTM D445	40	55	73
Viscosity Index	ASTM D2270	179	186	192
Density at 15°C (g/cm ³)	ASTM D1298	0.85	0.85	0.85
Pour Point (°C)	ASTM D97	-20	-24	-42
Flash Point (°C)	ASTM D92	268	272	279
Copper Strip Corrosion 3h @ 100°C	ASTM D130	1a	1a	1a
Demulsibility (minutes)	ASTM D1401	20	25	28
4 Ball Wear Scar Diameter (mm)	ASTM D4172	0.34	0.31	0.33
Temperature Range (°C)	-	-5 to 160	-10 to 160	-5 to 160
Shelf Life	-	5 years in original sealed containers whilst stored out of direct sunlight		



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on 

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717