

VICKERLUBE FGS SIL SPRAY



DESCRIPTION

VICKERLUBE FGS SIL SPRAY is a high performance, food grade, multipurpose, silicone lubricant spray. It is registered to H1 for incidental food contact for use in and around food, beverage and pharmaceutical processing and production areas.

APPLICATIONS

VICKERLUBE FGS SIL SPRAY is designed for all applications where a light, wet film, long life lubricant is required in the food and other clean industries such as cosmetics and the pharmaceutical industry. It is an excellent non-stick lubricant with very good high temperature resistance. It has very good water, chemical and oxidation resistance properties.

Applications include: -

- Slideways and chutes
- Chains
- Linkages, pins and other components
- Corrosion protection
- Multipurpose light lubrication

CERTIFICATION



VICKERLUBE FGS SIL SPRAY is NSF H1 Registered for incidental food contact, manufactured to ISO 9001:2015 and meets the requirements of FDA 21 CFR 178.3570.

Registration No. 160653

FEATURES AND BENEFITS

- | | |
|---|--|
| <ul style="list-style-type: none">• NSF H1 Registered• Light adhesive lubricant• Excellent wear protection• Oxidation and corrosion inhibited• Excellent water resistance• High Temperature resistance | <ul style="list-style-type: none">• Safe to use where incidental food contact may occur• Stays in place and reduces reapplication• Elongates component life• Increases product life & protects against corrosion• Elongates component life• Safe in elevated temperatures |
|---|--|

BENJⁿ R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717



Trusted for Generations

H.S.T.N: 34031910
REF: MKT.PDS.110
REV: 2

VICKERLUBE FGS SIL SPRAY



METHOD OF APPLICATION

Shake can thoroughly before use. Apply a thin, even coating onto surface from approximately 15 – 30 cm (6 to 12 inches). Apply VICKERLUBE FGS SIL SPRAY sparingly. Store in a cool, dry place, out of direct sunlight. Storage temperature should be below 50°C.

DO NOT USE ON SILICONE RUBBER

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FGS SIL SPRAY	RESULT
Appearance	Clear liquid
Base Oil	Silicone oil
Propellant	Propane / Butane
Service Temperature Range (°C)	-50°C to 200°C
Shelf Life	5 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717