

VICKERLUBE SOCK

46



Textiles

DESCRIPTION

Mineral based needle lubricant for the lubrication of sock knitting machinery.

APPLICATIONS

VICKERLUBE SOCK 46 can be applied by any method normally employed on sock knitting machines including circulatory oil systems, mist or spray systems or by manual oiling.

APPLICATION DETAILS

VICKERLUBE SOCK 46 is designed to provide a high standard of lubrication of sock machine knitting elements and has very good stability and resistance to oxidation. The oil is self-emulsifiable and readily removed in scouring from cotton or synthetic fibres.

PERFORMANCE DATA

- Readily scorable. Scouring under mildly alkaline conditions gives the best results on cotton.
- Expected to minimize swelling of elastomeric seals on knitting machinery.

NOTES

When introducing a new oil into a machine we recommend cleaning the original oil from the machine and oiler units as thoroughly as possible, to avoid the potential for any incompatibility problems.

TYPICAL CHARACTERISTICS AND PROPERTIES

| VICKERLUBE SOCK 46 | UNITS | TYPICAL RESULT |
|--------------------|-------|---|
| Colour | | Fluid yellow oil |
| Viscosity @ 40°C | cSt | Approx. 46 |
| Density @ 15°C | kg/l | Approx. 0.862 |
| Cloud Point | °C | < 0 |
| Setting Point | °C | < 0 |
| Flash Point | °C | > 170 |
| Ionic Character | | Nonionic / Cationic |
| Emulsifiability | | Emulsifies but not designed for application as emulsion |
| Shelf Life | | 7 years in original container stored out of direct sunlight |


Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJ^M R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom
Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: techserv@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717