

BIOGEAR XP RANGE



DESCRIPTION

BIOGEAR XP is a range of biodegradable, high performance, extreme pressure (EP) gear oils. These fluids are based on fully saturated esters with a high degree of renewability. The range has been designed for use in all types of enclosed gears and bearings. The use of base oils with an inherently high Viscosity Index (VI) and low pour point makes these products suitable for use over a wide temperature range.



EU Ecolabel : UK/027/024

The BIOGEAR XP range has been awarded the European Ecolabel for lubricants.

It achieves a biodegradability of >60% in the 28-day OECD 301B test, is non-toxic in aquatic environments and meets the US EPA's definition of an Environmentally Acceptable Lubricant (EAL).

The EU Ecolabel is a label of environmental excellence that is awarded to products and services meeting high environmental standards throughout their life-cycle: from raw material extraction, to production, distribution and disposal.

APPLICATIONS

BIOGEAR XP is designed for use in heavily loaded gearboxes operating at wide temperature ranges. It can be used in off-highway equipment, process gear cases and planetary transmissions, especially in sensitive environments where there is potential for fluid loss to occur.

CERTIFICATION

- DIN 51517 Part 3 (2018)
- ISO 12925-1:1996

COMPATIBILITY

Miscible with mineral oil and synthetic esters but, in accordance with best practice, it is recommended that the previous oil be fully drained and the system ideally flushed. Vickers do not recommend the mixing of oils.

Compatible with standard NBR, HNBR and FKM seal elastomers. Compatible with PTFE and PU80 / PU90 polyurethane samples as tested, but testing of specific grades of polyurethane is advised.

BENJⁿ R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

BIOGEAR XP RANGE



FEATURES AND BENEFITS

- Biodegradable Reduced environmental impact in the event of spillage
- Outstanding oxidation stability Less sludge and longer fluid life
- Wide operating temperature range Extends life at temperature extremes
- Excellent thermal stability Less fluid thickening and system failures
- Excellent demulsification Readily separates from water
- Good shear stability Less viscosity loss and fewer fluid changes
- High micropitting resistance Protects gears, even when subject to high loads

TYPICAL CHARACTERISTICS AND PROPERTIES

BIOGEAR XP RANGE	TEST METHOD	220	320	460
Appearance	Visual	Clear & bright	Clear & bright	Clear & bright
Viscosity at 40°C (cSt)	ASTM D7042	220	320	460
Viscosity at 100°C (cSt)	ASTM D7042	26.8	36.3	48.6
Viscosity Index	ASTM D2270	155	160	165
Pour Point (°C)	ASTM D7346	-36	-42	-36
Flash Point (°C)	ASTM D92	>200	>200	>200
Copper Corrosion 3h @ 100°C	ASTM D130	1a	1a	1a
Ageing 312hr@95°C, KV100 incr. (%)	ISO 4263-4	<6	<6	<6
FZG Scuffing (FLS)	ISO 14635-1	>14	>14	>14
FE8, Bearing Wear (mg)	DIN 51519-3	<30	<30	<30
Micropitting	FVA 54	>LS10, GFT high	>LS10, GFT high	>LS10, GFT high
Density @15°C (kg/l)	ASTM D4052	0.938	0.954	0.960

Shelf Life

5 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717