

# VICKERLUBE FG UNIVERSAL OIL 15









## DESCRIPTION

VICKERLUBE FG UNIVERSAL OIL 15 is a premium quality, medicinal white oil registered to 3H for direct and H1 for incidental food contact, for use in and around food, beverage, and pharmaceutical production areas.

## CERTIFICATION

VICKERLUBE FG UNIVERSAL OIL 15 is NSF 3H and H1 Registered -160895, Halal Certified, Kosher Certified, and meets the requirements of FDA 21 CFR 172.878 and 21 CFR 178.3620(a).

 <b>NSF</b>	 <b>HALAL</b>	 <b>KOSHER</b>	 <b>PART NUMBER</b>
<b>3H, H1 Registered</b>			<b>45251</b>

## APPLICATIONS

VICKERLUBE FG UNIVERSAL OIL 15 is designed for use in the food, beverage and pharmaceutical industries where there is a chance of direct food contact.

It is primarily intended for wash down and short term (overnight) corrosion protection and light lubrication for food manufacturing equipment.

## METHOD OF APPLICATION

VICKERLUBE FG UNIVERSAL OIL 15 can be applied manually by brush, in a trigger spray or pressurised lubrication system capable of pumping an ISO VG 15 fluid.

## FEATURES AND BENEFITS

- 3H and H1 Registered
- 3H direct contact registered
- Protects against corrosion
- Non-odour or tainting

Safe to use where direct or incidental food contact may occur  
After application, production can start immediately, no need to remove  
Increased component life  
No effect on food stuff

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on 

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard





Trusted for Generations

H.S.T.N: 27101985  
REF: MKT.PDS.114  
REV: 2

# VICKERLUBE FG UNIVERSAL OIL 15



## TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG UNIVERSAL OIL 15	TEST METHOD	RESULT
Appearance	Visual	Clear and Bright
Density at 15°C (g/cm <sup>3</sup> )	ASTM D4052	0.84
Viscosity @ 40°C (cSt)	ASTM D7042	15
Flash Point - COC (°C)	ASTM D92	196
Pour Point (°C)	ASTM D7356	-30
Shelf Life		3 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on   

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717